



ویژگی های اختیاری:

ویژگی های استاندارد:

Hydraulic Blade Tension

Proximity Switch For Sensing Blade Slippage

3 Mt Motorized Roller Table

Inverter

3 Mt Material Roller Table

Control Panel

Hydraulic Top Clamping

Sensitive Pressure

Lazer Line Pointer

Saw Blade 34

ILC Microspray Device

Coolant Pump

Security Switch

Optical Height Adjustment

Synchronisation Moveable Arm/Vice

Hydromechnic Blade Tension

Linear Guides

Heavy Duty Gearbox

3 inclined Blade

Saw Blade Brash

To Adjust Degree Panel

Hydraulic Vice

PARAMETER	UNIT	UNIT
Round Cutting Capacity	mm	360
Flat Cutting Capacity	mm	640 x 360
Square Cutting Capacity	mm	360
+30° Round Cutting Capacity	mm	360
+30° Flat Cutting Capacity	mm	510 x 360
+30° Square Cutting Capacity	mm	360
+45° Round Cutting Capacity	mm	360
+45° Flat Cutting Capacity	mm	390 x 360
+45° Square Cutting Capacity	mm	360
+60° Round Cutting Capacity	mm	310
+60° Flat Cutting Capacity	mm	250 x 360
+60° Square Cutting Capacity	mm	270
-30° Round Cutting Capacity	mm	360
-30° Flat Cutting Capacity	mm	510 x 360
-30° Square Cutting Capacity	mm	360
-45 Round Cutting Capacity	mm	360
-45° Flat Cutting Capacity	mm	390 x 360
-45° Square Cutting Capacity	mm	360
Main Drive Motor	kW	3
Hydraulic Motor	kW	1,1
Coolant Pump	kW	0,12
Cutting Speeds	m/min.	20 – 100
Band Dimensions	mm	5000x34x1,1
Working Height	mm	800
Weight	kg	1995
Length	mm	3000
Width	mm	1200
Height	mm	1910