

BMSY-560DG

مشخصات فنی دستگاه اره نواری برش دو طرفه BMSY-560DG



ویژگی های اختیاری:

Hydraulic Blade Tension

3 Mt Material Roller Table

3 Mt Motorized Roller Table

Hydraulic Top Clamping

ILC Microspray Device

Lazer Line Pointer

Chip Conveyor

ویژگی های استاندارد:

Heavy Duty Gearbox

Hydromechanic Blade Tension

Optical Height Adjustment

Saw Blade Brush

Sensitive Pressure

Synchronisation Moveable Arm/Vice

Inverter

Control Panel

Saw Blade 41

3 inclined Blade

Turn Table

Lineer Way

Security Switch

Proximity switch for sensing blade slippage

Hydraulic Vice

PARAMETER	UNIT	UNIT
Round Cutting Capacity	mm	560
Flat Cutting Capacity	mm	820 x 540
Square Cutting Capacity	mm	540
+30° Flat Cutting Capacity	mm	670 x 540
+30° Square Cutting Capacity	mm	540
+30° Round Cutting Capacity	mm	560
+45° Round Cutting Capacity	mm	550
+45° Flat Cutting Capacity	mm	520 x 540
+45° Square Cutting Capacity	mm	520
+60° Round Cutting Capacity	mm	340
+60° Flat Cutting Capacity	mm	340 x 520
+60° Square Cutting Capacity	mm	340
-30° Round Cutting Capacity	mm	500
-30° Flat Cutting Capacity	mm	670 x 540
-30° Square Cutting Capacity	mm	540
-45 Round Cutting Capacity	mm	520
-45° Flat Cutting Capacity	mm	520 x 540
-45° Square Cutting Capacity	mm	520
Main Drive Motor	kW	4
Hydraulic Motor	kW	1,1
Coolant Pump	kW	0,12
Band Dimensions	mm	6800x41x1,3
Working Height	mm	880
Weight	Kg	3200
Cutting Speeds	m/min	20 – 100
Lenght	mm	3800
Width	mm	1750
Height	mm	2350