

BMSY-650DG NC

مشخصات فنی دستگاه اره نواری برش دو طرفه BMSY-650DG NC



ویژگی های اختیاری:

Lazer Line Pointer

3 Mt Material Roller Table

3 Mt Motorized Roller Table

ILC Microspray Device

Hydraulic Top Clamping

45° / 60° 1,2 Mt Material Roller Table

ویژگی های استاندارد:

Saw Blade 54

Turn Table

Safety Rope Sensor

Hydraulic Vice

Motorized Swarf Brush

Security Switch

Synchronisation Moveable Arm/Vice

NC rotation table

Sensitive Pressure

Hydraulic Blade Tension

Inverter

Chip Conveyor

Linear Way

Optical Height Adjustment

Proximity switch for sensing blade slippage

Heavy Duty Gearbox

PARAMETER	UNIT	UNIT
Round Cutting Capacity	mm	650
Flat Cutting Capacity	mm	1000 x 600
Square Cutting Capacity	mm	600
+30° Round Cutting Capacity	mm	650
+30° Flat Cutting Capacity	mm	840 x 600
+30° Square Cutting Capacity	mm	600
+45° Round Cutting Capacity	mm	650
+45° Flat Cutting Capacity	mm	660 x 600
+45° Square Cutting Capacity	mm	600
+60° Round Cutting Capacity	mm	440
+60° Flat Cutting Capacity	mm	440 x 600
+60° Square Cutting Capacity	mm	440
-30° Round Cutting Capacity	mm	650
-30° Flat Cutting Capacity	mm	840 x 600
-30° Square Cutting Capacity	mm	600
-45° Round Cutting Capacity	mm	650
-45° Flat Cutting Capacity	mm	660 x 600
-45° Square Cutting Capacity	mm	600
Main Drive Motor	kW	7,5
Hydraulic Motor	kW	4
Coolant Pump	kW	0,12
rotating motor	kW	0,37
Chip Conveyor Motor	kW	0,25
Motorized Swarf Brush	kW	0,18
Cutting Speeds	m/min.	20 – 100
Band Dimensions	mm	8400x54x1,6
Working Height	mm	880
Weight	kg	6250
Lenght	mm	4750
Width	mm	2270
Height	mm	2630